



Rocking Piston Compressors



KM-60C



KM-120C



KM-200C

Features

- Oil-less Piston
- Continuous or intermittent duty
- 115 or 230 volt
- 230 volt option allows 50 or 60 HZ
- Quiet operation
- 6 ft. power cord
- 2 year limited warranty
- Thermal overload protection
- Ramped internal valve plate allows for restart under load after power failures
- All six models have CE. Every model except the KM-200C (120V only) has UL/CSA

Model	KM-60C	KM-60HC	KM-120C	KM-120HC	KM-200C	KM-200HC
HP	1/4		1/2		3/4	
Volt / Hz	115V / 60 Hz	230V / 60 Hz	115V / 60 Hz	230V / 60 Hz	115V / 60 Hz	230V / 60 Hz
Amp @ 0 PSI	2.2	1.1	3.0	1.5	5.4	3.1
Amp @ 20 PSI	3.2	1.6	4.0	2.0	6.9	3.7
Dimensions (in.)	7.1 x 6.3 x 7.8		9.4 x 6.3 x 7.8		10.8 x 6.5 x 9.5	
Weight (lbs.)	16		19		28	
Air Flow at PSI	CFM		CFM		CFM	
0	3.8		5.5		7.4	
5	3.4		4.9		7.2	
10	3.2		4.8		6.8	
15	3.1		4.5		6.7	
20	2.9		4.2		6.4	
25	2.7		4.0		6.2	
30	2.6		3.6		6.0	
40	2.4		3.2		5.6	
50	2.2		2.7		5.0	

Notes:

- Actual Results may vary based on power and environmental conditions

Package Includes

- 40 PSI Pressure Relief Valve
- Intake Air Filter Assembly
- Brass Hose Fitting
- Vibration mounts

Box includes Model:

- | | |
|----------------------------------|-----------------------------------|
| <input type="checkbox"/> KM-60C | <input type="checkbox"/> KM-60HC |
| <input type="checkbox"/> KM-120C | <input type="checkbox"/> KM-120HC |
| <input type="checkbox"/> KM-200C | <input type="checkbox"/> KM-200HC |

